




- 开门角度: 105度 ± 3度
- 关门角度: 86度 ± 2度
- 铰杯厚度: 11.8毫米
- 铰杯直径: 35毫米
- 面板(K)尺寸: 3毫米
- Opening angle: 105° ± 3°
- Closing angle: 86° ± 2°
- Depth of hinge cup: 11.8mm
- Diameter of hinge cup: 35mm
- Drilling distance on the door(K): 3mm

S6D01美式铰链系列功能图 Installation dimensions

S6D01-1 1"



盖位 Overlay D=1"




产品型号 Item No.	K=3 盖位(Overlay) (D+0.3)
S6D01-1	25.4

S6D01-034 3/4"



盖位 Overlay D=3/4"




产品型号 Item No.	K=3 盖位(Overlay) (D+0.3)
S6D01-034	19

S6D01-058 5/8"




盖位 Overlay D=5/8"




产品型号 Item No.	K=3 盖位(Overlay) (D+0.3)
S6D01-058	15.8





铰杯种类 Hinge cup types



缓冲器 Damper types



可配螺丝种类 Options of screws and dowels

 3.5x16 螺丝代码: 3.5x16 Screw code: 3.5x16	 4x16 螺丝代码: 4x16 Screw code: 4x16
 M8胶粒 M8 Dowel 胶粒代码: R2286螺母 Dowel code: R2286 dowel	 M10胶粒 M10 Dowel 胶粒代码: 103螺母 Dowel code: 103 dowel

S6D01 SOFT-CLOSING COMPACT HINGE

美式内置缓冲铰链




- 开门角度: 105度 ± 3度
- 关门角度: 86度 ± 2度
- 铰杯厚度: 11.8毫米
- 铰杯直径: 35毫米
- 面板(K)尺寸: 3毫米
- Opening angle: 105° ± 3°
- Closing angle: 86° ± 2°
- Depth of hinge cup: 11.8mm
- Diameter of hinge cup: 35mm
- Drilling distance on the door(K): 3mm

S6D01美式铰链系列功能图 Installation dimensions




盖位 Overlay D=1/2"



产品型号 Item No.	K=3 盖位(Overlay) (D+0.3)
S6D01-012	12.7




盖位 Overlay D=7/16"




产品型号 Item No.	K=3 盖位(Overlay) (D+0.3)
S6D01-0716	11.1

铰杯种类 Hinge cup types



缓冲器 Damper types



可配螺丝种类 Options of screws and dowels

<p>3.5x16 螺丝代码: 3.5x16 Screw code: 3.5x16</p>	<p>4x16 螺丝代码: 4x16 Screw code: 4x16</p>
<p>M8胶粒 M8 Dowel 胶粒代码: R2286螺母 Dowel code: R2286 dowel</p>	<p>M10胶粒 M10 Dowel 胶粒代码: 103螺母 Dowel code: 103 dowel</p>




- 开门角度: 105度 ± 3度
- 关门角度: 86度 ± 2度
- 铰杯厚度: 11.8毫米
- 铰杯直径: 35毫米
- 面板(K)尺寸: 3毫米
- Opening angle: 105° ± 3°
- Closing angle: 86° ± 2°
- Depth of hinge cup: 11.8mm
- Diameter of hinge cup: 35mm
- Drilling distance on the door(K): 3mm

S6D02美式铰链系列功能图 Installation dimensions



S6D02-112 1-1/2"

盖位 Overlay D=1-1/2"




产品型号 Item No.	K=3 盖位(Overlay) (D+0.3)
S6D02-112	38.1



S6D02-138 1-3/8"

盖位 Overlay D=1-3/8"




产品型号 Item No.	K=3 盖位(Overlay) (D+0.3)
S6D02-138	34.9




S6D02-1516 1-5/16"

盖位 Overlay D=1-5/16"




产品型号 Item No.	K=3 盖位(Overlay) (D+0.3)
S6D02-1516	33.3

铰杯种类 Hinge cup types



缓冲器 Damper types



内置 Inner

可配螺丝种类 Options of screws and dowels

<p>3.5x16 螺丝代码: 3.5x16 Screw code: 3.5x16</p>	<p>4x16 螺丝代码: 4x16 Screw code: 4x16</p>
<p>M8胶粒 M8 Dowel 胶粒代码: R2286螺母 Dowel code: R2286 dowel</p>	<p>M10胶粒 M10 Dowel 胶粒代码: 103螺母 Dowel code: 103 dowel</p>




- 开门角度: 105度 ± 3度
- 关门角度: 86度 ± 2度
- 铰杯厚度: 11.8毫米
- 铰杯直径: 35毫米
- 面板(K)尺寸: 3毫米
- Opening angle: 105° ± 3°
- Closing angle: 86° ± 2°
- Depth of hinge cup: 11.8mm
- Diameter of hinge cup: 35mm
- Drilling distance on the door(K): 3mm

S6D02美式铰链系列功能图 Installation dimensions

S6D02-114 1-1/4"



盖位 Overlay D=1-1/4"




产品型号 Item No.	K=3 盖位(Overlay) (D+0.3)
S6D02-114	31.8

S6D02-1 1"



盖位 Overlay D=1"




产品型号 Item No.	K=3 盖位(Overlay) (D+0.3)
S6D02-1	25.4

S6D02-058 5/8"



盖位 Overlay D=5/8"




产品型号 Item No.	K=3 盖位(Overlay) (D+0.3)
S6D02-058	15.9

S6D02-012 1/2"




盖位 Overlay D=1/2"




产品型号 Item No.	K=3 盖位(Overlay) (D+0.3)
S6D02-012	12.7

铰杯种类 Hinge cup types



缓冲器 Damper types



内置 Inner

可配螺丝种类 Options of screws and dowels

<p>3.5x16 螺丝代码: 3.5x16 Screw code: 3.5x16</p>	<p>4x16 螺丝代码: 4x16 Screw code: 4x16</p>
<p>M8胶粒 M8 Dowel 胶粒代码: R2286螺母 Dowel code: R2286 dowel</p>	<p>M10胶粒 M10 Dowel 胶粒代码: 103螺母 Dowel code: 103 dowel</p>